



019-8004 through 019-8007

Kernmantle Rope HLL : Cross Arm Straps

FEATURES :

- 2 Person HLL System
- Available in lengths from 30' to 100'
- Abrasion-resistant kernmantle rope:
Tensile Strength: 11,261lbs
- Secure rope tensioner
- Web energy absorber with protective cover reduces impact forces
- Convenient carry and storage bag

PERSONAL ATTACHMENT POINT(S)

- 2 O-rings
Minimum Breaking Strength: 5,000lbs

SYSTEM ATTACHMENT POINT(S)

- 2 Carabiners
Gate Rating: 3,600lbs
Minimum Breaking Strength: 5,000lbs
- 2 Cross Arm Straps
Minimum Breaking Strength: 5,000lbs

ITEM WEIGHT :

- Weight Varies per length



USER WEIGHT CAPACITY	
ANSI	130-310lbs (140.6kg) per person; 2 Person maximum
OSHA	420lbs (190.5kg) per person; 1 Person maximum

STANDARD COMPLIANT WITH	
ANSI	N/A
OSHA	1926.502, 1910.140, 1910.66

SIZE(S)	
019-8004	30 Feet (10.8lbs)
019-8005	60 Feet (13.8lbs)
019-8006	80 Feet (15.8lbs)
019-8007	100 Feet (17.8lbs)

COMPONENT	MATERIAL SPECIFICATION
Rope	16mm Kernmantle Rope
Rope Tensioner	YCM Plated Steel
Energy Absorber	Polyester
O-rings	Clear Zinc Plated Steel
Carabiners	YCM Plated Steel
Bag	Polyester
Cross-Arm Strap	Polyester Webbing with YCM Plated Steel