



THUMB CROTCH REINFORCEMENT



CUT
EN388



4442C



Tested for harmful substances
according to Oeko-Tex® Standard 100
SH40 096266 TESTEX

ATTRIBUTES:

LINER

13g Dark Blue Engineered
A3 Liner

COATING

Black HCT® Nano-Foam
Nitrile Palm Coating

FEATURES:

- Reinforced Thumb Crotch
- Nano-Foam Coating Provides Unparalleled Dexterity and Tactile Sensitivity
- Excellent Dry Grip

APPLICATIONS:

- Automotive Manufacturing
- Sheet Metal Handling
- Construction
- Metal Stamping
- Glass Handling

Armor Guys reference number : 04-350

CATEGORY:

Extraflex

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES:



SPECIFICATIONS

LINER MATERIALS	13g Dark Blue Engineered A3 Liner
COATING MATERIALS	Black HCT® Nano-Foam Nitrile
WRIST DESIGN	Continuous Knit
SIZES	XS-XXL

PACKAGING

CASE SIZE	XS	S	M	L	XL	XXL
PER CARTON	10DZ	10DZ	10DZ	10DZ	10DZ	10DZ
CASE WEIGHT	13.22/lbs	13.66/lbs	14.10/lbs	15.42/lbs	16.08/lbs	17.18/lbs
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4442C	EN Level 4 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F